

### AMENDMENT TO THE CLAIMS

Please **CANCEL** claim 23.

Please **AMEND** claims 1, 8, 10, 11, 14, 17, 18, 19 and 22 as follows.

A copy of all pending claims and a status of the claims are provided below.

1. (currently amended) A package divert mechanism, comprising:  
a frame member adapted for use with an existing conveyor system for transporting an item in an original direction; and  
a moveable diverting mechanism extending from the frame member, the moveable diverting mechanism being movable substantially perpendicular to the original direction of travel of the item being transported on the existing conveyor system and diverting the item in either a first direction or a second opposing ~~and aligned~~ direction with respect to the first direction, the moveable diverting mechanism includes a blade mechanism extending from the frame member to divert the item in either the first direction or the second opposing direction.

2. (previously presented) The package divert mechanism of claim 1, wherein:  
the moveable diverting mechanism is a bi-directional moveable diverting mechanism;  
and  
the first direction and the second opposing direction are both substantially perpendicular to the original direction of travel of the item.

3. (previously presented) The package divert mechanism of claim 1, wherein the moveable diverting mechanism remains stationary so that the item can pass therethrough.

4. (previously presented) The package divert mechanism of claim 1, wherein the moveable diverting mechanism includes a downward extending blade having a first surface and a second surface adapted for diverting the item and a longitudinal axis, the first and second surface

facing opposing directions substantially perpendicular to the original direction of travel of the item and the longitudinal axis is substantially parallel to the original direction of travel of the item.

5. (original) The package divert mechanism of claim 1, wherein the moveable diverting mechanism further includes a moving mechanism for moving the moveable diverting mechanism.

6. (original) The package divert mechanism of claim 5, wherein the moving mechanism includes an actuator and a gliding mechanism.

7. (previously presented) The package divert mechanism of claim 1, further comprising a frame member of the frame and a mounting mechanism of the moveable diverting mechanism, a gliding mechanism extending from the frame member and connected to the mount of the moveable diverting mechanism.

8. (original) ~~The package divert mechanism of claim 5, further comprising~~ A package divert mechanism, comprising:

a frame member adapted for use with an existing conveyor system for transporting an item in an original direction;

a moveable diverting mechanism extending from the frame member, the moveable diverting mechanism being movable substantially perpendicular to the original direction of travel of the item being transported on the existing conveyor system and diverting the item in either a first direction or a second opposing direction; and

an over current sensor for determining whether a current associated with the actuator exceeds a threshold limit,

wherein the moveable diverting mechanism further includes a moving mechanism for moving the moveable diverting mechanism.

9. (original) The package divert mechanism of claim 1, further comprising a plurality of sensors associated with the moveable diverting mechanism.

10. (currently amended) ~~The package divert mechanism of claim 9,~~ A package divert mechanism, comprising:

a frame member adapted for use with an existing conveyor system for transporting an item in an original direction;

a moveable diverting mechanism extending from the frame member, the moveable diverting mechanism being movable substantially perpendicular to the original direction of travel of the item being transported on the existing conveyor system and diverting the item in either a first direction or a second opposing direction; and

a plurality of sensors associated with the moveable diverting mechanism, wherein the plurality of sensors include:

at least one home sensor for detecting a home position of the moveable diverting mechanism;

at least one over travel sensor for detecting an over travel position of the moveable diverting mechanism; and

at least one photosensor for detecting a flow of the items.

11. (currently amended) ~~The package divert mechanism of claim 1, further comprising A~~ package divert mechanism, comprising:

a frame member adapted for use with an existing conveyor system for transporting an item in an original direction;

a moveable diverting mechanism extending from the frame member, the moveable diverting mechanism being movable substantially perpendicular to the original direction of travel of the item being transported on the existing conveyor system and diverting the item in either a first direction or a second opposing direction; and

momentary contacts which provide an input signal to control the movement of the moveable diverting mechanism.

12. (previously presented) A package divert mechanism, comprising:

a frame member adapted for use with an existing conveyor system for transporting an item in an original direction;

a moveable diverting mechanism extending from the frame member, the moveable diverting mechanism being movable substantially perpendicular to the original direction of travel of the item being transported on the existing conveyor system and diverting the item in either a first direction or a second opposing direction; and

hoods having openings, the hoods being positioned at an entrance and each exit of the frame.

13. (original) The package divert mechanism of claim 12, further comprising at least one interlock switch for detecting a position of the hoods and providing a signal to a controller for shutting down movement of the moveable diverting mechanism when any of the hoods are in an upright position.

14. (currently amended) A bi-directional divert mechanism, comprising:

a frame having an entrance and a plurality of exits;

a gliding mechanism extending across a frame member of the frame and adapted to move between opposing exits of the plurality of exits; and

a downward extending moveable blade member coupled to the gliding mechanism, the downward extending blade member having opposing blade surfaces to divert an item in either a first direction or a second direction opposing the first direction, and further having a longitudinal axis, the opposing blade surfaces facing opposing exits and the longitudinal axis extending in a direction between the entrance and another of the exits.

15. (original) The bi-directional divert mechanism of claim 14, further comprising a series of sensors for monitoring or controlling actions of the downward extending moveable blade member.

16. (original) The bi-directional divert mechanism of claim 15, wherein the series of sensors includes at least one of:

at least one home sensor for detecting a home position of the downward extending moveable blade member;

at least one over travel sensor for detecting an over travel position of the downward extending moveable blade member;

at least one photosensor for detecting a flow of items;

an over current sensor for determining whether a current associated with an actuator of the downward extending moveable blade member exceeds a threshold limit; and

momentary contacts which provide an input signal to control the movement of the downward extending moveable blade member.

17. (currently amended) ~~The bi-directional divert mechanism of claim 14, further comprising~~ A bi-directional divert mechanism, comprising:

a frame having an entrance and a plurality of exits;

a gliding mechanism extending across a frame member of the frame and adapted to move between opposing exits of the plurality of exits;

a downward extending moveable blade member coupled to the gliding mechanism, the downward extending single blade member having opposing blade surfaces and a longitudinal axis, the opposing blade surfaces facing opposing exits and the longitudinal axis extending in a direction between the entrance and another of the exits; and

a safety hood positioned at least at one of the entrance and exits of the frame.

18. (currently amended) A method of diverting an item, comprising the steps of:

locating a first home position and a second home position of a diverting mechanism having a blade;

positioning the diverting mechanism at one of the first home position and the second home position;

determining a diverting direction of the item based on classification information associated with the item; and

controlling the diverting mechanism in accordance with the diverting direction to divert an item in either a first exit or a second exit.

19. (currently amended) The method of claim 18, wherein the controlling step includes: moving the diverting mechanism in a first direction in order to divert the item in the first direction which is substantially perpendicular to an original direction of travel of the item; moving the diverting mechanism in a second direction opposite the first direction; and allowing the diverting mechanism to remain stationary in order to allow the item to pass through unimpeded.

20. (original) The method of claim 19, further comprising the step of determining and allocating a new home position of the diverting mechanism after the controlling step.

21. (original) The method of claim 18, further comprising the step of suspending movement of the diverting mechanism based on at least one of:

- a detection of an item being jammed;
- a detection of an item exceeding a threshold physical characteristic limit;
- a detection that the diverting mechanism exceeds a travel limit; and
- a detection that an operator has open access to the diverting mechanism.

22. (currently amended) ~~The method of claim 21,~~ A method of diverting an item, comprising the steps of:

locating a first home position and a second home position of a diverting mechanism;  
positioning the diverting mechanism at one of the first home position and the second  
home position;

determining a diverting direction of the item based on classification information  
associated with the item; and

controlling the diverting mechanism in accordance with the diverting direction; and  
suspending movement of the diverting mechanism based on at least one of:

a detection of an item being jammed;

a detection of an item exceeding a threshold physical characteristic limit;

a detection that the diverting mechanism exceeds a travel limit; and

a detection that an operator has open access to the diverting mechanism

wherein the step of the detection of the jammed item and the detection of the item exceeding a threshold physical characteristic limit is based on a detection of an over current of an actuator which moves the diverting mechanism.

23. (cancel)